


**Evopave™
Specification**



The choice for equine.

Evopave™ Rubber Interlocking pavers are fully elastic, weather proof, water permeable, frost proof, durable and slip resistant, designed for equine use. Evopave™ are made of tough rubber particles that are bound by a MDI polyurethane binder.

Name	Evopave™ Interlocking Rubber Pavers		
Description	Prefabricated moulded rubber interlocking pavers composed of recycled rubber particles and MDI polyurethane resin binder		
Dimensions [plan]	200 mm x 160/115 mm [7 7/8 in x 6 9/32 in/ 4 1/2 in]		
Thickness	15-45 mm [5/8in-1 3/4 in]		
Density	800 kg/m ³ [49.9 lb/ft ³]		
Traction Coefficient	Dry 1.0 μ	Wet 1.0 μ	Rating: Good
Slip Resistance [μ]	Dry 75 μ	Wet 44 μ	Rating: Good
Abrasion Resistance 5000 Revs.	0.10 g	[0.0035 oz]	Rating: Good
Fatigue Resistance [New]	No Cracking or Fracture		
Spike Resistance	Grade 2 - Up to 50,000 revs.		
	Surface repairable under routine maintenance		
Resistance to Indentation	0.64 mm	[0.025 in]	Rating: Good
Resistance to Air Ageing	0.18 g	[0.0063 oz]	Rating: Good
Fatigue Resistance [after Air Ageing]	No Cracking or Fracture		
Resistance to Water Ageing	0.36 g	[0.0127 oz]	Rating: Good
Fatigue Resistance [after Water Ageing]	No Cracking or Fracture		
Resistance to Artificial Weathering	0.20 g	[0.0070 oz]	Rating: Good
Fatigue Resistance [after Artificial Weathering]	No Cracking or Fracture		
Resistance to Ozone	No Cracking or Fracture		
Flammability	Class 1 (DIN 51920)		
Infiltration Rate	285 mm/hr	[11.2 in/hr]	



www.rephouse.com